

teXXmo *your ticket to mobility!*

# KALEO DT301T



teXXmo

Mobile Solution  
GmbH & Co. KG  
Otto-Lilienthal-Str. 36  
D-71034 Böblingen

fon +49 70 31-71 48 50  
fax +49 70 31-71 48 49

[www.teXXmo.com](http://www.teXXmo.com)  
[info@teXXmo.com](mailto:info@teXXmo.com)

# KALEO DT301C

System - System	
CPU <i>Prozessor</i>	Intel® 6th Generation Core™ i5 or i7 processor
RAM <i>Arbeitsspeicher</i>	8GB
Storage <i>Festplattenkapazität</i>	128GB to 1TB Flash
Operating System <i>Betriebssystem</i>	Microsoft® Windows® 7 Pro, Windows® 10 IoT Enterprise; 64bit
Display <i>Bildschirm</i>	25,7 cm (10,1") LED-backlight screen with capacitive touch
Display Resolution <i>Bildschirmauflösung</i>	1920 x 1200 (WUXGA)
Network <i>Netzwerk</i>	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band; Bluetooth 4.0 LE
NIST Compliant <i>NIST Compliant</i>	Yes, capacitive touch stylus (optional)
Control Switch and Button <i>Tasten</i>	1 power button, 3 programmable buttons ,RF switch
Indicator <i>Anzeigen</i>	1 power/ battery status LED
Speaker <i>Lautsprecher</i>	Built-in speaker
Camera <i>Kamera</i>	5 megapixel back camera with auto focus
I/O Ports - Anschlüsse	
USB 3.0 Port <i>USB 3.0 Anschluss</i>	1
Audio Jack <i>Audio-Buchse</i>	1
Power-in <i>Stromanschluß</i>	1
Smart Card Reader <i>Smart Card Leser</i>	Full-slot, reads ISO 7816 T=0, T=1; EMV 2000 certified, 1.8/3/5V smart card
Mechanical and Environmental - Umgebung	
AC/DC Adapter <i>Netzteil</i>	Input: 100 – 240V AC; Output: 19V DC, 3.42A
Battery Pack <i>Akkupack</i>	Hot swappable battery, 11.4V, 5400mAh, Hot swappable battery, 11.4V, 8000mAh (optional)
Enclosure <i>Gehäuse</i>	ABS + PC plastics and magnesium-aluminum alloy
Stylus <i>Stift</i>	Capacitive touch stylus or digital pen
Dimensions (H x W x D) <i>Abmessungen (H x B x T)</i>	198 x 280 x 41 mm
Weight <i>Gewicht</i>	1.4 kg
Water and Dust Resistance <i>Schutz gegen Nässe u. Staub</i>	IP65
Shock and Vibration <i>Schock und Vibration</i>	MIL-STD-810G
EMI and EMC Tolerance <i>EMI und EMV Toleranz</i>	MIL-STD-461F
Anti Explosion <i>Explosionsschutz</i>	Class 1 Division 2 (C1D2, optional)
Regulatory <i>Zertifizierungen</i>	CE, RoHS compliant
Temperature <i>Temperatur</i>	Operation:-20°C - 60°C; Storage:-55°C - 70°C
Humidity <i>Luftfeuchtigkeit</i>	0% – 90% non-condensing
Options - Optionen	
Camera <i>Kamera</i>	5 megapixel front camera
Barcode Scanner (2D) <i>Barcode Scanner (2D)</i>	2D barcode scanner; reads 1D also
WWAN <i>WWAN</i>	4G module for LTE, HSPA+, GSM/GPRS/EDGE, EV-DO, Rev A and 1xRTT
GNSS Module <i>GNSS Modul</i>	U-blox M8 GNSS module with concurrent reception of GPS and GLONASS, industry leading -167dBm navigation sensitivity
Long Range Bluetooth <i>Langstrecken Bluetooth</i>	Class 1 Bluetooth (~300 m)



Desktop Charging Cradle



Wall/Vehicle Cradle



Stylus



Battery Gang Charger



5-Bay Cabinet Charger



Shoulder Strap



Detachable Keyboard



DC/DC-Adapter



Protective Foils



Battery Charger Kit

teXXmo

Mobile Solution  
GmbH & Co. KG  
Otto-Lilienthal-Str. 36  
D-71034 Böblingen

fon +49 70 31-71 48 50  
fax +49 70 31-71 48 49

www.teXXmo.com  
info@teXXmo.com